Submittal Data Sheet



Roth Part #	Item Description	Manufacturer	
See Below	HKV Manifold Set	Roth Industries, Inc.	

Job	Engineer
Contractor	Representative

Application:

Distribution and control of flow and heat output to various radiant and/or hydronic tubing loops or zones.

Technical Specifications:

Manifold Body Material Brass

Manifold Body Size

1" (25.4 mm)

Height

15" (380 mm)

Depth

3 1/2" (89 mm)

Maximum Flow Rate

10 gpm (37.7 lpm)

Maximum Operating Temperature


Maximum Operating Pressure

150 psi (10.3 bar)

Recommended Test Pressure

45 - 60 psi (3.1 - 4.1 bar)

Part #	Description	Length Inches (mm)
2315006883	HKV Manifold Set 2 Loops	10 1/4 (261)
2315006884	HKV Manifold Set 3 Loops	12 1/2' (318)
2315006885	HKV Manifold Set 4 Loops	14 1/2" (369)
2315006886	HKV Manifold Set 5 Loops	16 3/4" (426)
2315006887	HKV Manifold Set 6 Loops	18 3/4" (477)
2315006888	HKV Manifold Set 7 Loops	21" (533)
2315006889	HKV Manifold Set 8 Loops	23" (585)
2315006891	HKV Manifold Set 10 Loops	27 1/4" (693)



Product Information:

Supply manifold contains manual flow adjustment and stop valves.

Return manifold contains valve assemblies for isolation or for mounting thermostat controlled valve actuators.

Drain, fill and vent valves can be mounted on either side of manifold.

Interchangeable, galvanized steel mounting brackets with rubber vibration isolator pads.

Supply and return manifolds are offset.

Supply and Return transition fittings can be mounted on either side of manifold.

Will accommodate 3/8", 1/2", 5/8" PE-RT, PEX, PEX-AL-PEX and PERT-AL-PERT tubing.

Effective Date: November 2011