

Submittal Data Sheet



Part #	Description
See Below	CM, HK & HKV Manifold Set Tubing Fitting Assemblies

Project Information

Job Name:

Location:

Date Submitted:

Engineer:

Submitted by:

Contractor:

Approved by:

Manufacturer's Representative:

Application

Attaches PE-RT, PEX and PERT-AL-PERT tubing to the Roth CM, HK and HKV manifolds.

Used with specialized fittings to couple tubing, transition to copper and transition from manifold supply/return trunk to PERT/PEX tubing.



Product Information

Assembly includes:

Brass compression nut

Brass split ring

Barbed fitting (various styles and sizes) x Euroconical fitting with o-ring

Technical Information

Manifold connection	- R20 Thread (3/4" nominal)
Maximum operating pressure *	- 145psi (10 bar)
Maximum operating temperature*	- 230°F (110°C)
Maximum tightening torque	- 59 ft. lbs. (80 Nm)

* - Same as manifold

Part Numbers

	Part Number	Description	Weight lbs (kg)
PE-RT/PEX Tubing Fitting Assemblies			
<input type="checkbox"/>	2335001410	For 3/8" PE-RT/PEX Tubing	1 (0.5)
<input type="checkbox"/>	2335003021	For 1/2" PE-RT/PEX Tubing	1.5 (0.7)
<input type="checkbox"/>	2335003022	For 5/8" PE-RT/PEX Tubing	2 (0.9)
ALuLaser Plus Tubing Fitting Assemblies			
<input type="checkbox"/>	2347131300	For 3/8" ALuLaser Plus Tubing	1 (0.5)
<input type="checkbox"/>	2347002331	For 1/2" ALuLaser Plus Tubing	1.5 (0.7)
<input type="checkbox"/>	2347002332	For 5/8" ALuLaser Plus Tubing	2 (0.9)

Note: Tubing Fitting Assemblies also available for 3/4" PE-RT/PEX tubing. See separate submittal for information.

Contact Information

Roth Industries, Inc. 268 Bellew Ave. S. Watertown, NY 13601

Telephone: US (888) 266-7684 Canada (800) 969-7684 Fax: US & Canada (866) 462-2914

www.roth-america.com